


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86 SA Suspension Led bianco 46W + 2x39W Diff - Direct+Indirect Emission - anodized



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

ВЫБРАТЬ

FLUO LED

anodized




КОД ПРОДУКТА

M2903N60

Вид светового потока



Luminaire comes complete with power supply and DALI control unit .

ТЕХНИЧЕСКИЕ ДАННЫЕ	
<div><div>ХАРАКТЕРИСТИКИ</div><div>Наименование продукции: Nothing86 SA Suspension Led bianco 46W + 2x39W Diff - Direct+Indirect Emission - anodized</div><div>Код: M2903N60</div><div>Цвет: anodized</div><div>Материал: Extruded Aluminium</div><div>Серии: Architectural</div><div>Окружающая среда: Внутреннее</div></div> <div><div>РАЗМЕРЫ</div><div><div><div>Длина: cm 237</div><div>Ширина: cm 9.2</div><div>Высота: cm 12.5</div><div>Максимальная высота от потолка: cm 200</div><div>тест раскаленной проволокой: 650 °</div></div><div><div>РАЗМЕРЫ</div><div></div></div><div><div>ЦВЕТ</div><div></div></div></div><div><div>ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ</div><div>Категория: LED</div><div>Ватт: 40W</div><div>Световой поток (lm): 5200lm</div><div>Типология: 1</div><div>Цветовая температура (K): 4000K</div><div>Класс: A</div></div><div><div>ЛАМПЫ НЕ ВКЛЮЧЕНЫ В КОМПЛЕКТ</div><div><div> Категория: FLUO</div><div>Количество: 2</div><div>Lbs: T16</div><div>Ватт: 39W</div><div>Цоколь: G5</div><div>Тип: FDH-39</div></div></div></div>	

Световой поток (lm):3100lm

Цветопередача:85

Цветовая температура (K):3000K

LUMINAIR

ПРА:Electronic Integrated

Наличие трансформатора:with DALI control

Watt:46W + 2x39W

Напряжение:220V-240V

АКСЕССУАРЫ



LAMPE FLUO T5 39W HO
3000°K M004380

LAMPE FLUO T5 39W HO
4000°K Ø16 G5 M004381