


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Nothing86System SA Ceiling Led Direct - 23W 4000K Undimmable - Anodized



ДИЗАЙН:

Ernesto Gismondi

МАТЕРИАЛЫ:

Extruded Aluminium

ОПИСАНИЕ:

A versatile modular lighting system for linear diffused or dark light emission and freely configurable accent lighting. Composed of structural modules in extruded aluminium, prewired gear plates and optics systems. 3 types of installation: recessed, surface mounting and suspended. Structural modules available in 12 different lengths of up to 4736mm, specially designed to allow the lighting designer to alternate as freely as possible different light sources. The lighting sequence can also evolve over time to meet new arrangements, as long as it remains compatible with the initial total length installed. Linear fluorescent, led and metal halide technologies can be freely alternated. Prewired gear plates with quick-connectors, with direct fluorescent or LED lighting equipment, and indirect fluorescent illumination. 2 options of fluorescent diffused lighting available: T16-seamless lamps or conventional T16 lamps with overlapping arrangement for uninterrupted light lines without dark spots. 2 LED equipment options: monochromatic with warm white or neutral white emission, and RGB. Angular configurations possible by means of junction angles on the same plane or on 2 perpendicular planes (on request). Simple installations can be managed with "all-in-one" fixtures (nothing 86Stand-Alone) already pre-configured and fully accessorized. Complies with standard EN60598-1 and other specific standards.

ВЫБРАТЬ

LED

Anodized

КОД ПРОДУКТА

M2904N60

Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции:

Nothing86System SA Ceiling Led Direct - 23W 4000K Undimmable - Anodized

Код:

M2904N60

Цвет:

Anodized

Материал:

Extruded Aluminium

Серии:

Architectural

Окружающая среда:

Внутреннее

место контракта:

Гостеприимство  
Гостиницы, Розничные магазины, Офисы

РАЗМЕРЫ

Длина:

cm 118

Ширина:

cm 9.2

Высота:

cm 12.5

тест раскаленной проволокой:

850 °

РАЗМЕРЫ

1188/2372

125

92

ЦВЕТ

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория:

LED

Ватт:

20W

Световой поток (lm):

2600lm

Типология:

1

Цветовая температура (K):

4000K

Класс:

A

LUMINAIR

ПРА:

Electronic Dimmable Dali Integrated

Watt:

23W

Напряжение:

220V-240V

