

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Parabola80_round_12W_52°_4000K_Silver



ДИЗАЙН:

Artemide
2010

МАТЕРИАЛЫ:

Aluminium

ОПИСАНИЕ:

•Light fixture with high-performance LED light sources. Ceiling installation. Composed by: frame, body, lens, fixing springs. Frame in injection mould of aluminium. Heat sink body in extruded aluminium. Lens in polycarbonate with 3 different versions of beam. Fixing springs in harmonic steel. White monochromatic LEDs available in 3 colour temperatures: Warm = 3000K Neutral = 4000K Electrical connection to the driver by means of a FEP-FEP cable and a terminal board. IP Rating IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions..

ВЫБРАТЬ

LED

Silver

КОД ПРОДУКТА

NL1906340W002

Вид светового потока

IP40

ТЕХНИЧЕСКИЕ ДАННЫЕ


ХАРАКТЕРИСТИКИ

Наименование продукции: Parabola80_round_12W_52°_4000K_Silver
Код: NL1906340W002
Цвет: Silver
Материал: Aluminium
Серии: Architectural
Окружающая среда: Внутреннее
место контракта: Гостеприимство Гостиницы, Гостеприимство Рестораны, Розничные магазины, Офисы, Музеи & Выставки, Частные резиденции

РАЗМЕРЫ

Диаметр: см 7.5
Глубина встройки: см 8.7
Форма отверстия: Круглая форма

РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LED Категория: LED COB
Ватт: 12W
Световой поток (lm): 1391
Типология: 1
Цветовая температура (K): 4000K
Класс: A

LUMINAIR

Watt: 12W

АКСЕССУАРЫ



ALIMENT. 20W 350mA (indip.)
NL19033



ALIMENT. 25W DIMM 1/10V
PUSH+CAV.SINC. NL62810



ALIMENTATORE 16.8W
350/500/700MA DALI NL104210

