

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Parabola80\_Adjustable round\_12W\_52°\_2700K\_Silver



ДИЗАЙН:

Artemide  
2010

МАТЕРИАЛЫ:

Aluminium

ОПИСАНИЕ:

•Light fixture with high-performance LED light sources. Ceiling installation. Composed by: frame, body, lens, fixing springs. Frame in injection mould of aluminium. Heat sink body in extruded aluminium. Lens in polycarbonate with 3 different versions of beam. Fixing springs in harmonic steel. White monochromatic LEDs available in 3 colour temperatures: Warm = 3000K Neutral = 4000K Electrical connection to the driver by means of a FEP-FEP cable and a terminal board. IP Rating IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions..

ВЫБРАТЬ

LED

Silver

КОД ПРОДУКТА

NL1906440Y002

Вид светового потока


IP40

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Parabola80\_Adjustable round\_12W\_52°\_2700K\_Silver  
Код: NL1906440Y002  
Цвет: Silver  
Материал: Aluminium  
Серии: Architectural  
Окружающая среда: Внутреннее  
место контракта: Гостеприимство Гостиницы, Гостеприимство Рестораны, Розничные магазины, Офисы, Музеи & Выставки, Частные резиденции

РАЗМЕРЫ



РАЗМЕРЫ

Диаметр: 88 mm  
Глубина встройки: 87 mm  
Форма отверстия: Круглая форма

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LED Категория: LED COB  
Ватт: 12W  
Световой поток (lm): 990lm  
Типология: 1  
Цветовая температура (K): 2700K  
Класс: A

ЦВЕТ



LUMINAIR

Watt: 12W

АКСЕССУАРЫ



ALIMENT. 20W 350mA (indip.)  
NL19033



ALIMENT. 25W DIMM 1/10V  
PUSH+CAV.SINC. NL62810



ALIMENTATORE 16.8W  
350/500/700MA DALI NL104210

