

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Parabola80_Adjustable round_12W_76°_3000K_Black



ДИЗАЙН:

Artemide
2010

МАТЕРИАЛЫ:

Aluminium

ОПИСАНИЕ:

•Light fixture with high-performance LED light sources. Ceiling installation. Composed by: frame, body, lens, fixing springs. Frame in injection mould of aluminium. Heat sink body in extruded aluminium. Lens in polycarbonate with 3 different versions of beam. Fixing springs in harmonic steel. White monochromatic LEDs available in 3 colour temperatures: Warm = 3000K Neutral = 4000K Electrical connection to the driver by means of a FEP-FEP cable and a terminal board. IP Rating IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions..

ВЫБРАТЬ

LED

Black

КОД ПРОДУКТА

NL1906480K004

Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ


ХАРАКТЕРИСТИКИ

Наименование продукции:	Parabola80_Adjustable round_12W_76°_3000K_Black
Код:	NL1906480K004
Цвет:	Black
Материал:	Aluminium
Серии:	Architectural
Окружающая среда:	Внутреннее
место контракта:	Гостеприимство Гостиницы, Гостеприимство Рестораны, Розничные магазины, Офисы, Музеи & Выставки, Частные резиденции

РАЗМЕРЫ

Диаметр:	cm 7.5
Глубина встройки:	cm 8.7
Форма отверстия:	Круглая форма

РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LED	Категория:	LED COB
	Ватт:	12W
	Световой поток (lm):	1336lm
	Типология:	1
	Цветовая температура (K):	3000K
	Класс:	A

LUMINAIR

Watt:	12W
-------	-----

АКСЕССУАРЫ



ALIMENT. 20W 350mA (indip.)
NL19033



ALIMENT. 25W DIMM 1/10V
PUSH+CAV.SINC. NL62810



ALIMENTATORE 16.8W
350/500/700MA DALI NL104210

