

## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Parabola55\_Square\_3W\_58°\_4000K\_White



#### ДИЗАЙН:

Artemide  
2010

#### МАТЕРИАЛЫ:

Aluminium

#### ОПИСАНИЕ:

• Light fixture with high-performance LED light sources. • Ceiling installation. • Composed by: frame, body, lens, fixing springs. • Frame in injection mould of aluminium. • Heat sink body in extruded aluminium. • Lens in polycarbonate with 3 different versions of beam. • Fixing springs in harmonic steel. • White monochromatic LEDs available in 3 colours temperatures: Very Warm = 2700K Warm = 3000K Neutral = 4000K • Electrical connection to the driver by means of a FEP-FEP cable and a terminal board. • IP Rating IP40. • Insulation class III. • Technical features of light fixtures in compliance with EN60598-1. • Installation must be carried out by specialized personnel. • Carefully follow the instructions.

#### ВЫБРАТЬ

LED

White

#### КОД ПРОДУКТА

NL1906960W006

#### Вид светового потока



IP40

#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Parabola55\_Square\_3W\_58°\_4000K\_White

Код: NL1906960W006

Цвет: White

Материал: Aluminium

Серии: Architectural

Окружающая среда: Внутреннее

место контракта: Гостеприимство Гостиницы, Розничные магазины, Офисы, Музеи & Выставки, Частные резиденции

##### ЦВЕТ



##### РАЗМЕРЫ

Длина: см 5,5

Ширина: см 5,5

Глубина встройки: см 6

Форма отверстия: Квадратная форма

Вес: kg 0,2

##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED COB

Ватт: 3W

Световой поток (lm): 361lm

Типология: 1

Цветовая температура (K): 4000K

Класс: A

##### LUMINAIR

ПРА: Driver non fornito

Watt: 3W

#### АКСЕССУАРЫ

No Image Available

No Image Available

No Image Available

ALIMENT. 20W 350mA (indip.)  
NL19033

ALIMENT. 25W DIMM 1/10V  
PUSH+CAV.SINC. NL62810

ALIMENTATORE 16.8W  
350/500/700MA DALI NL104210

