

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Parabola55_Adjustable round_3W_58°_3000K_Silver



ДИЗАЙН:

Artemide
2010

МАТЕРИАЛЫ:

Aluminium

ОПИСАНИЕ:

• Light fixture with high-performance LED light sources. • Ceiling installation. • Composed by: frame, body, lens, fixing springs. • Frame in injection mould of aluminium. • Heat sink body in extruded aluminium. • Lens in polycarbonate with 3 different versions of beam. • Fixing springs in harmonic steel. • White monochromatic LEDs available in 3 colours temperatures: Very Warm = 2700K Warm = 3000K Neutral = 4000K • Electrical connection to the driver by means of a FEP-FEP cable and a terminal board. • IP Rating IP40. • Insulation class III. • Technical features of light fixtures in compliance with EN60598-1. • Installation must be carried out by specialized personnel. • Carefully follow the instructions.

ВЫБРАТЬ

LED

Silver

КОД ПРОДУКТА

NL1907060K002

Вид светового потока



IP40

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции:	Parabola55_Adjustable round_3W_58°_3000K_Silver
Код:	NL1907060K002
Цвет:	Silver
Материал:	Aluminium
Серии:	Architectural
Окружающая среда:	Внутреннее
место контракта:	Гостеприимство Гостиницы, Розничные магазины, Офисы, Музеи & Выставки, Частные резиденции

ЦВЕТ



РАЗМЕРЫ

Диаметр:	cm 6.4
Глубина встройки:	cm 6.2
Форма отверстия:	Круглая форма
Вес:	kg 0.2

ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория:	LED COB
Ватт:	3W
Световой поток (lm):	345lm
Количество:	1 x 1
Типология:	1
Цветовая температура (K):	3000K
Класс:	A

LUMINAIR

ПРА:	Driver non fornito
Watt:	3W

АКСЕССУАРЫ



ALIMENT. 20W 350mA (indip.)
NL19033



ALIMENT. 25W DIMM 1/10V
PUSH+CAV.SINC. NL62810



ALIMENTATORE 16.8W
350/500/700MA DALI NL104210

