

ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Parabola80_square_12W_64°_2700K_Black



ДИЗАЙН:

Artemide
2010

МАТЕРИАЛЫ:

Aluminium

ОПИСАНИЕ:

•Light fixture with high-performance LED light sources. Ceiling installation. Composed by: frame, body, lens, fixing springs. Frame in injection mould of aluminium. Heat sink body in extruded aluminium. Lens in polycarbonate with 3 different versions of beam. Fixing springs in harmonic steel. White monochromatic LEDs available in 3 colour temperatures: Warm = 3000K Neutral = 4000K Electrical connection to the driver by means of a FEP-FEP cable and a terminal board. IP Rating IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions..

ВЫБРАТЬ

LED

Black

КОД ПРОДУКТА

NL1907160Y004

Вид светового потока

IP40

ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Parabola80_square_12W_64°_2700K_Black

Код: NL1907160Y004

Цвет: Black

Материал: Aluminium

Серии: Architectural

Окружающая среда: Внутреннее

место контракта: Гостеприимство Гостиницы,
Гостеприимство Рестораны, Розничные магазины, Офисы, Музеи & Выставки,
Частные резиденции

РАЗМЕРЫ


Длина: см 7.5

Ширина: см 7.5

Глубина встройки: см 8.8

Форма отверстия: Квадратная форма

РАЗМЕРЫ



ЦВЕТ



ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

LED	Категория:	LED COB
	Ватт:	12W
	Световой поток (lm):	990lm
	Типология:	1
	Цветовая температура (K):	2700K
	Класс:	A

LUMINAIR

Watt: 12W

АКСЕССУАРЫ



ALIMENT. 20W 350mA (indip.)
NL19033

ALIMENT. 25W DIMM 1/10V
PUSH+CAV.SINC. NL62810

ALIMENTATORE 16.8W
350/500/700MA DALI NL104210

