


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Spike RGB - 14°x34°



ДИЗАЙН:
Artemide
2011

МАТЕРИАЛЫ:
Aluminium, transparent tempered glass.

ОПИСАНИЕ:
Light fixture with high-performance LED light sources. Wall/ceiling installation. Monochromatic version or RGB version. Body in extruded EN AW6060 T5 aluminium. Diffuser in 3mm-thick transparent tempered glass. Diffuser in 1,5mm-thick transparent polycarbonate. Stoppers in die-cast aluminium with silicone gasket. Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version). 24Vdc remote ballast. Painted profile with 2-stage outdoor treatment: primer, outdoor paint. Antidazzle screen in painted extruded aluminium, upon request. Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K RGB version with red, green and blue monochromatic LEDs. IP Rating IP65. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel.

ВЫБРАТЬ

LED

Aluminium

КОД ПРОДУКТА

NL17075ELC

Вид светового потока



ТЕХНИЧЕСКИЕ ДАННЫЕ	
ХАРАКТЕРИСТИКИ Наименование продукции: Spike RGB - 14°x34° Код: NL17075ELC Цвет: Aluminium Материал: Aluminium, transparent tempered glass. Серии: Outdoor РАЗМЕРЫ 800 5 35 45 ЦВЕТ	
РАЗМЕРЫ Длина: cm 80 Ширина: cm 4.5 Высота: cm 4 Форма отверстия: Прямоугольная форма Вес: kg 1 ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ Категория: LED Ватт: 25,2W Типология: 1 Цветовая температура (K): RGB Класс: A Напряжение: 24 Vdc LUMINAIR ПРА: Remote electronic Watt: 25,2W Напряжение: 24Vdc	

NO
IMAGE
AVAILABLE

DRIVER LED NLX 2-50 RGB
50W NL19050

NO
IMAGE
AVAILABLE

DRIVER LED NLX 2-75 RGB
75W NL75190

NO
IMAGE
AVAILABLE

DRIVER LED NLX 2-100 RGB
100W NL82030

NO
IMAGE
AVAILABLE

DRIVER LED NLX 2-150 RGB
150W NL80220

NO
IMAGE
AVAILABLE

DSC30 interfaccia USB - DMX
stand alone microled NL19030

NO
IMAGE
AVAILABLE

Alimentatore 9V/350mA con
connettore mini USB per
DSC30 NL19031

NO
IMAGE
AVAILABLE

CAVO COLLEGAMENTO
TASTIERA ESTERNA NL7833