


## ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

### Spike RGB - 25°



#### ДИЗАЙН:

Nord Light  
2011

#### МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

#### ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Wall/ceiling installation. Monochromatic version or RGB version. Body in extruded EN AW6060 T5 aluminium. Diffuser in 3mm-thick transparent tempered glass. Stoppers in die-cast aluminium with silicone gasket. Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version). 24Vdc remote ballast. Painted profile with 2-stage outdoor treatment: primer, outdoor paint. Antidazzle screen in painted extruded aluminium, upon request. Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K RGB version with red, green and blue monochromatic LEDs. IP Rating IP65. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel.

#### ВЫБРАТЬ

LED

Aluminium

#### КОД ПРОДУКТА

NL5003130C002

#### Вид светового потока

IP65



#### ТЕХНИЧЕСКИЕ ДАННЫЕ

##### ХАРАКТЕРИСТИКИ

Наименование продукции: Spike RGB - 25°  
Код: NL5003130C002  
Цвет: Aluminium  
Материал: Aluminium, transparent tempered glass.  
Серии: Nord Light, Outdoor  
место контракта: Фасады зданий

##### РАЗМЕРЫ

Длина: cm 78  
Высота: cm 4.2  
Диаметр базы: cm 3.5


##### ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED  
Ватт: 25,2W  
Типология: 1  
Цветовая температура (К): RGB  
Класс: A  
Напряжение: 24 Vdc

##### LUMINAIR

ПРА: Remote electronic  
Watt: 25,2W  
Напряжение: 24Vdc

##### РАЗМЕРЫ



##### ЦВЕТ



#### АКСЕССУАРЫ



DRIVER LED NLX 2-70 IP65



DRIVER LED NLX 2-100 RGB



CAVO COLLEGAMENTO



SPIKE RGB 78 SCHERMO

NL81260

100W IP65 NL84100

TASTIERA ESTERNA NL7833

ANTIABBAGLIAMENTO  
NL50035



DSC30 interfaccia USB - DMX  
stand alone microled NL19030



Alimentatore 9V/350mA con  
connettore mini USB per  
DSC30 NL19031



DRIVER LED NLX 2-150  
Max150W IP65 NL77270