


ТЕХНИЧЕСКИЕ ДАННЫЕ ПРОДУКТА

Spike RGB - 40°



ДИЗАЙН:

Nord Light
2011

МАТЕРИАЛЫ:

Aluminium, transparent tempered glass.

ОПИСАНИЕ:

Light fixture with high-performance LED light sources. Wall/ceiling installation. Monochromatic version or RGB version. Body in extruded EN AW6060 T5 aluminium. Diffuser in 3mm-thick transparent tempered glass. Stoppers in die-cast aluminium with silicone gasket. Adjustable brackets in aluminium. Electrical connection to the ballast by means of a H05RN-F (monochrome) or a 4-poles sylicon/rubber cable (RGB), with IP68 terminal board supplied with the fixture (IP65 version). 24Vdc remote ballast. Painted profile with 2-stage outdoor treatment: primer, outdoor paint. Antidazzle screen in painted extruded aluminium, upon request. Optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K RGB version with red, green and blue monochromatic LEDs. IP Rating IP65. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel.

ВЫБРАТЬ

LED

Aluminium

КОД ПРОДУКТА

NL5003140C002

Вид светового потока

IP65



ТЕХНИЧЕСКИЕ ДАННЫЕ

ХАРАКТЕРИСТИКИ

Наименование продукции: Spike RGB - 40°
Код: NL5003140C002
Цвет: Aluminium
Материал: Aluminium, transparent tempered glass.
Серии: Nord Light, Outdoor
место контракта: Фасады зданий

РАЗМЕРЫ

Длина: cm 78
Высота: cm 4.2
Диаметр базы: cm 3.5


ЛАМПЫ ВКЛЮЧЕНЫ В КОМПЛЕКТ

Категория: LED
Ватт: 25,2W
Типология: 1
Цветовая температура (К): RGB
Класс: A
Напряжение: 24 Vdc

LUMINAIR

ПРА: Remote electronic
Watt: 25,2W
Напряжение: 24Vdc

РАЗМЕРЫ



ЦВЕТ



АКСЕССУАРЫ



DRIVER LED NLX 2-70 IP65



DRIVER LED NLX 2-100 RGB



CAVO COLLEGAMENTO



SPIKE RGB 78 SCHERMO

NL81260

100W IP65 NL84100

TASTIERA ESTERNA NL7833

ANTIABBAGLIAMENTO
NL50035



DSC30 interfaccia USB - DMX
stand alone microled NL19030



Alimentatore 9V/350mA con
connettore mini USB per
DSC30 NL19031



DRIVER LED NLX 2-150
Max150W IP65 NL77270