

PHOTO: S. W. 72-50
<http://www.schubring.it>


STAKE

1.0

LED 8W | 220-240VAC | 50-60Hz
 COB2-step | incl. PS | phase-cut dim
 aluminium powder coated

CE 0.55kg \oplus 960° IP54 \approx 0.3 \oplus

0-120°



3000K | >80CRI | 480lm | 1m cable


727174D4

2.0

LED 8W | 220-240VAC | 50-60Hz
 COB2-step | incl. PS | phase-cut dim
 aluminium powder coated


CE 0.50kg \oplus 960° IP54 \approx 0.3 \oplus

0-120°



3000K | >80CRI | 480lm

727374D4



OPTIONAL
 groundspike **90013106**
 snoot **90019004**

ALWAYS USE
 base 200 **910042D0**
 base 400 **910044D0**

OPTIONAL
 groundspike **90013107**
 snoot **90019004**



EXTERIOR | FLOOR PROJECTOR

STAKE FOLD


1.0

LED 8W | 220-240VAC | 50-60Hz
COB2-step | incl. PS | phase-cut dim
aluminium powder coated

CE 0.78kg \oplus 960° IP54 \approx 0.3 \oplus

 \curvearrowright 0-90°





3000K | >80CRI | 480lm

 **727274D4**

OPTIONAL
groundspike **90013107**

snoot **90019004**

