

STRANGE

INTERIOR | CEILING RECESSED

1.0 LED


LED 7/10W | 350-500mA
 COB 3-step | excl. power supply
 aluminium powder coated

CE 0.43kg TE 960° IP20 $\approx 0,3$

86x86

35°/35° 95

355° 4-25



131161W_

131161B_

LIGHT COLOUR

2200K | >80CRI | 315-465lm | 15Vf 1

2700K | >90CRI | 420-590lm | 18Vf 3

3000K | >90CRI | 470-640lm | 18Vf 5

ALWAYS USE

plaster kit 90017116

power supply
 350mA | 10W 90213402

500mA | 10W 90214403

power supply phase-cut dim
 500mA | 15W 90224501

more power supplies on page 490

1.0 PAR16


PAR16 max. 50W | GU10
 220-240VAC | 50-60Hz
 aluminium powder coated

CE 0.41kg 960° IP20 $\approx 0,9$

86x86

35°/35° 120

355° 4-25



131120W0

131120B0

ALWAYS USE

plaster kit 90017116

OPTIONAL

PAR16 LED GU10 6W phase-cut dim
 2700K 390lm 901228W2

3000K 410lm 901228W4

PAR16 LED GU10 7W ambient white dim
 1800-3000K 901229S9

2.0 LED


2xLED 7/10W | 350-500mA | 18Vf
 COB 3-step | excl. power supply
 aluminium powder coated

CE 0.74kg TE 960° IP20 $\approx 0,3$

86x156

35°/35° 95

355° 4-25



131261W_

131261B_

LIGHT COLOUR

2200K | >80CRI | 2x315-465lm | 15Vf 1

2700K | >90CRI | 2x420-590lm | 18Vf 3

3000K | >90CRI | 2x470-640lm | 18Vf 5

ALWAYS USE

plaster kit 90017117

power supply
 350mA | 10W 90213402

500mA | 10W 90214403

power supply phase-cut dim
 500mA | 15W 90224501

more power supplies on page 490

2.0 PAR16


2xPAR16 max. 50W | GU10
 220-240VAC | 50-60Hz
 aluminium powder coated

CE 0.70kg 960° IP20 $\approx 0,9$

86x156

35°/35° 120

355° 4-25



131220W0

131220B0

ALWAYS USE

plaster kit 90017117

OPTIONAL

PAR16 LED GU10 6W phase-cut dim
 2700K 390lm 901228W2

3000K 410lm 901228W4

PAR16 LED GU10 7W ambient white dim
 1800-3000K 901229S9



STRANGE

1.0 LED111


LED 13W | 220-240V | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

CE 1.03 kg □ TE 960° IP20 $\approx 0,9$

□ 154x154

∩ 35°/35° ≈ 90

↻ 355° $\approx 4-25$



1.0 ES111


ES111 max. 75W | GU10
220-240V | VAC | 50-60Hz
aluminium powder coated

CE 0.75 kg □ 960° IP20 $\approx 0,9$

□ 154x154

∩ 35°/35° ≈ 135

↻ 355° $\approx 4-25$



1.0 QR111


QR111 max. 75W | G53 | 12V
excl. transformer
aluminium powder coated

CE 0.75 kg □ TE 960° IP20 $\approx 0,9$

□ 154x154

∩ 35°/35° ≈ 90

↻ 355° $\approx 4-25$



LIGHT COLOUR

2700K | >80CRI | 640lm **2**

3000K | >80CRI | 680lm **4**

OPTIONAL

ES111 LED GU10 13W phase-cut dim
2700K 530lm **901528S2**

3000K 540lm **901528S4**

ALWAYS USE

transformer
12V | 60W **90221902**

12V | 105W **90221903**

ALWAYS USE

plaster kit **90017118**

ALWAYS USE

plaster kit **90017118**

ALWAYS USE

plaster kit **90017118**